

Effectiveness of Stormwater Retention Ponds in Controlling Urban Runoff

Lauren Hallett
Dr. Gregory Hancock,
Advisor
William and Mary REU
program

August 2, 2006




This presentation discusses the effectiveness of stormwater retention ponds and their impact on stream temperature



Role of retention ponds in controlling urban runoff




Empirical evaluation of pond at Kensington Woods




Implications for pond modeling and design

Urbanization increases stormwater runoff rates and volume




Virginia specifies that 2 yr/24 hr storm post development peak outflows must be at 2 yr/24 pre development levels

Ponds are designed to increase inflow to outflow lag times



James City County stipulates a 24 hr centroid to centroid retention rate for 1 yr, 24 hr storms

Anatomy of a wet stormwater retention pond



Little oversight of ponds after they are built



06-05-2006

Our goal was to monitor actual retention ponds

Mulberry
(Cristina)

Ironbound
(Greg)

Pointe
(Brent)

Kensington
(Lauren)

Chambrel

W&M



Rainfall, pond elevation, and pond designs were used to establish discharge rates



Tipping bucket rain gauge




Pressure Transducer


+




Staff Gauge




Pond Designs




Rainfall



Pond Elevation



Discharge to Elevation Curve





Inflow and Outflow Hydrographs

Design-based elevation to discharge curves were verified with the salt dilution method



Storm-time conductivity measurements





Salt Concentration / Time
=> Volume / Time

Field results compared to plan
predictions


No 1 yr/24 hr storms occurred, yet peak flows frequently neared 1yr/24 hr levels

Kensington Storms, 2006







Occasional extreme maximum inflow and outflow points were also observed

Centroid to centroid lag times were low and project to be below regulations



Kensington Storms, 2006



Model better predicted ideal-type storms than non-ideal



Ideal-type: Day 112

Non-Ideal: Day 174



Design storms used in plans and modeled 2006 storms had below-regulation centroid lag times




Outflow from Ironbound warmed downstream temperatures



Ironbound Temperature vs Discharge, Storm Day 174





Ironbound/Chambrel Temperature, Storm Day 174



Ironbound temperatures were much higher than in Chambrel, the control stream

Mulberry outflow temperatures were lower than upstream and downstream



A large, unshaded retention pond is above Mulberry

Conclusions and Recommendations

Regulatory

Require centroid lags in the design plans

Future Research

Continue data collection, particularly salt dilution

Refine allowed modeling input data

Model temperature along a stream

Collect temperature data year round

Acknowledgements

Thanks to Dr. Gregory Hancock, Dr. Randolph Chambers, Timothy Russell, Tonya Insani, “Storm Team” Cristina Lopez, Brent Aigler, and Emily Hathaway, and The National Science Foundation

